# Parallelization of "stencil-based" methods: step-69 (and beyond)

Martin Kronbichler<sup>1</sup>, <u>Matthias Maier</u>, Ignacio Tomas<sup>2</sup>

Department of Mathematics Texas A&M University



<sup>1</sup> Institute for Computational Mechanics, TUM, Munich

<sup>2</sup> CSRI, Sandia National Laboratories

## Motivation

## Motivation

#### Simulation of hyperbolic systems of conservation laws



Goals:

### Outline

#### 1 Motivation

**2** The compressible Euler equations

#### **3** step-69

#### 4 . . . and beyond

## The compressible Euler equations

Hyperbolic system of conservation laws

 $\mathbf{u}_t + \operatorname{div} f(\mathbf{u}) = \mathbf{0},$ 

where  $\mathbf{u}(\mathbf{x}, t) : \mathbb{R}^d \times \mathbb{R} \to \mathbb{R}^{d+2}$ , and  $\mathbf{f}(\mathbf{u}) : \mathbb{R}^{d+2} \to \mathbb{R}^{(d+2) \times d}$ , with space dim.  $d \ge 1$ .

State: 
$$\mathbf{u} = \begin{bmatrix} \rho \\ \mathbf{m} \\ E \end{bmatrix}$$
 Flux:  $f(\mathbf{u}) = \begin{bmatrix} \mathbf{m}^{\top} \\ \rho^{-1}\mathbf{m} \otimes \mathbf{m} + \mathbb{I}\rho \\ \frac{\mathbf{m}^{\top}}{\rho}(E+\rho) \end{bmatrix}$ ,

Here  $\rho \in \mathbb{R}^+$  denotes the density,  $\mathbf{m} \in \mathbb{R}^d$  is the momentum, and  $E \in \mathbb{R}^+$  is the total energy of the system. The pressure  $p \in \mathbb{R}^+$  is determined by an equation of state, e.g.,

Polytropic gas equation: 
$$p(\mathbf{u}) := (\gamma - 1) \Big( E - rac{|\mathbf{m}|^2}{2\rho} \Big), \quad \gamma \in (1, 5/3].$$

Variational principle viable ??? Testing with **u**:

$$\frac{1}{2} \frac{\mathrm{d}}{\mathrm{d}t} \left\| \mathbf{u} \right\|_{L^{2}\Omega}^{2} + \underbrace{\left( \operatorname{div} f(\mathbf{u}), \mathbf{u} \right)_{L^{2}(\Omega)}}_{???} = 0.$$

- no energy estimate available
- no (quasi) best approximation
- etc.
- → none of the classical finite element toolbox available...

### Solution theory

We call  $\mathbf{u}$  a viscosity solution if

$$\mathbf{u} = \lim_{\varepsilon \to 0} \mathbf{u}^{\varepsilon}$$
,

with

$$\mathbf{u}_t^{\varepsilon} + \operatorname{div} f(\mathbf{u}^{\varepsilon}) = \varepsilon \Delta \mathbf{u}^{\varepsilon}.$$

 global existence and uniqueness of viscosity solutions is an open problem.

#### So what can we do?

#### What can we meaningfully expect?

#### Invariant set

If  $\mathbf{u}$  is a viscosity solution, then

 $\mathbf{u}(\mathbf{x}, t) \in \mathcal{B} \quad \forall \mathbf{x} \in \Omega, \ \forall t \ge 0,$ 

where  $\mathbf{u} \in \mathcal{B}$  implies

- positivity of density:  $\rho > 0$
- positivity of internal energy:

$$E-\frac{|\mathbf{m}|^2}{2\rho}>0$$

• local minimum principle on specific entropy:

 $s(\mathbf{u}) \geq \min_{x \in \Omega} s(\mathbf{u}_0(\mathbf{x}))$ 

### Conservation

Conservation of mass, momentum and total energy:

$$rac{\mathsf{d}}{\mathsf{d}t}\int_\Omega \mathbf{u}\,\mathsf{d}t + \int_{\partial\Omega} \mathbf{n}\cdot f(\mathbf{u})\,\mathsf{d}o_{\mathbf{x}} = 0.$$

→ Robustness: We want a numerical scheme that is conservative and maintains the invariant set.

#### How does (a subset of) the community judge our code?

Picture norm comparison of flow characteristics to (known) experimental results.





To summarize:

- Robustness: conservative and invariant domain preserving
   Most importantly: This implies that our scheme will never crash (no matter what mesh was used, or (admissible) initial data was prescribed)
- Accuracy (not discussed): second order convergent in case of known, smooth viscosity solutions
- Scalability: Large-scale 3D computation

• Guermond & Popov, Invariant domains and first-order continuous finite element approximation for hyperbolic systems, SIAM J. Numer. Anal. 54(4):2466-2489.

(Grossly oversimplified) formal derivation

Let  $\mathbf{u}_h(\mathbf{x}, t) = \sum_j \varphi_j(\mathbf{x}) \mathbf{U}_j(t)$  be a finite element approximation:

$$\frac{\mathrm{d}}{\mathrm{d}t}\left(\boldsymbol{\varphi}_{i},\mathbf{u}_{h}\right)+\left(\boldsymbol{\varphi}_{i},\operatorname{div}\mathbb{f}(\mathbf{u}_{h})\right) = 0.$$

Forward Euler:

$$\sum_{\boldsymbol{\in}\mathcal{I}(i)} m_{ij} \frac{\mathbf{U}_{j}^{n+1} - \mathbf{U}_{j}^{n}}{\tau_{n}} + \left(\boldsymbol{\varphi}_{i}, \operatorname{div} \mathbb{f}\left(\sum_{j \in \mathcal{I}(i)} \mathbf{U}_{j}^{n}\right)\right) = 0.$$

Lump mass matrix and approximate flux,  $f(\mathbf{u}_h^n) \approx \sum_j f(\mathbf{U}_j^n) \varphi_j$ :

$$m_i \frac{\mathbf{U}_i^{n+1} - \mathbf{U}_i^n}{\tau_n} + \sum_{j \in \mathcal{I}(i)} \mathbb{f}(\mathbf{U}_j^n) \cdot \mathbf{c}_{ij} = 0, \qquad m_i = \int_{\Omega} \varphi_i, \quad \mathbf{c}_{ij} = \int_{\Omega} \varphi_i \nabla \varphi_j.$$

• Guermond & Popov, Invariant domains and first-order continuous finite element approximation for hyperbolic systems, SIAM J. Numer. Anal. 54(4):2466-2489.

#### Scheme

$$m_i \frac{\mathbf{U}_i^{n+1} - \mathbf{U}_i^n}{\tau_n} + \sum_{j \in \mathcal{I}(i)} \mathbb{f}\left(\mathbf{U}_j^n\right) \cdot \mathbf{c}_{ij} - \sum_{j \in \mathcal{I}(i)} d_{ij}^n \mathbf{U}_j^n = 0,$$

where

$$m_i = \int_{\Omega} \varphi_i, \qquad \mathbf{c}_{ij} = \int_{\Omega} \varphi_i \nabla \varphi_j,$$

and where we have introduced a "graph viscosity"  $d_{ii}^n$  as stabilization term.

#### The correct construction of $d_{ij}^n$ is key for robustness

Compute two characteristic propagation speeds associated with  $U_i^n$  or  $U_i^n$ :

$$\lambda_{-}^{1}(\boldsymbol{U}_{j}^{n},\boldsymbol{p}^{*}) \coloneqq \tilde{u}_{i}^{n} - \tilde{c}_{i}^{n}\sqrt{1 + \frac{\gamma + 1}{2\gamma}\left[\frac{\boldsymbol{p}^{*} - \tilde{\boldsymbol{p}}_{i}^{n}}{\tilde{\boldsymbol{p}}_{i}^{n}}\right]_{\text{pos}}}, \ \lambda_{+}^{3}(\boldsymbol{U}_{j}^{n},\boldsymbol{p}^{*}) \coloneqq \tilde{u}_{j}^{n} + \tilde{c}_{j}^{n}\sqrt{1 + \frac{\gamma + 1}{2\gamma}\left[\frac{\boldsymbol{p}^{*} - \tilde{\boldsymbol{p}}_{j}^{n}}{\tilde{\boldsymbol{p}}_{j}^{n}}\right]_{\text{pos}}},$$

and a two-rarefaction pressure:

$$ilde{
ho}^{st}(oldsymbol{U}_{i}^{n},oldsymbol{U}_{j}^{n})= ilde{
ho}_{j}\,\left(rac{ ilde{c}_{i}+ ilde{c}_{j}-rac{\gamma-1}{2}ig( ilde{u}_{j}- ilde{u}_{i}ig)}{ ilde{c}_{i}\,ig(rac{ ilde{
ho}_{j}}{ ilde{
ho}_{j}}ig)^{-rac{\gamma-1}{2\,\gamma}}+ ilde{c}_{j}}
ight)^{rac{arepsilon_{j}}{\gamma-1}},$$

and a monotone increasing and concave down function

$$\psi(p) \coloneqq f(\boldsymbol{U}_{i}^{n}, p) + f(\boldsymbol{U}_{j}^{n}, p) + \tilde{u}_{j} - \tilde{u}_{i}, \qquad f(\boldsymbol{U}, p) \coloneqq \begin{cases} \frac{\sqrt{2}(p - \tilde{p})}{\sqrt{\tilde{p}[(\gamma + 1)p + (\gamma - 1)\tilde{p}]}} & \text{if } p \geq \tilde{p}, \\ \left[ (p/\tilde{p})^{\frac{\gamma - 1}{2\gamma}} - 1 \right] \frac{2\tilde{c}}{\gamma - 1}, & \text{otherwise.} \end{cases}$$

Now:

$$\tilde{\lambda}_{\max} = \max\left(\left[\lambda_{-}^{1}(\boldsymbol{U}_{i}^{n}, \boldsymbol{p}^{*})\right]_{\text{neg}}, \left[\lambda_{+}^{3}(\boldsymbol{U}_{j}^{n}, \boldsymbol{p}^{*})\right]_{\text{pos}}\right), \quad \boldsymbol{p}^{*} \coloneqq \begin{cases} \tilde{\boldsymbol{p}}^{*}(\boldsymbol{U}_{i}^{n}, \boldsymbol{U}_{j}^{n}) & \text{if } \psi(\boldsymbol{p}_{\max}) < 0, \\ \min(\tilde{\boldsymbol{p}}_{\max}, \tilde{\boldsymbol{p}}^{*}(\boldsymbol{U}_{i}^{n}, \boldsymbol{U}_{j}^{n})) & \text{otherwise.} \end{cases}$$

0 ---

### Scheme

$$\mathbf{U}_{i}^{n+1} = \mathbf{U}_{i}^{n} + \frac{\tau_{n}}{m_{i}} \Big( \sum_{j \in \mathcal{I}(i)} \operatorname{ff} \left( \mathbf{U}_{j}^{n} \right) \cdot \mathbf{c}_{ij} - \sum_{j \in \mathcal{I}(i)} d_{ij}^{n} \mathbf{U}_{j}^{n} \Big)$$

where 
$$m_i = \int_{\Omega} \varphi_i, \quad \mathbf{c}_{ij} = \int_{\Omega} \varphi_i \nabla \varphi_j, \quad d_{ij}^n = \max \left( \tilde{\lambda}_{\max}(\boldsymbol{n}_{ij}, \boldsymbol{U}_i^n, \boldsymbol{U}_j^n) | \boldsymbol{c}_{ij} |, \tilde{\lambda}_{\max}(\boldsymbol{n}_{ji}, \boldsymbol{U}_j^n, \boldsymbol{U}_j^n) | \boldsymbol{c}_{ji} | \right)$$

 $\mathcal{I}(i)$  — all column indices coupling to *i*.

Stencil based: compare to matrix-vector multiplication

$$y_i = \sum_{j \in \mathcal{I}(i)} a_{ij} x_j,$$

... but highly nonlinear!

euler step // Step 1: compute off-diagonal  $d_{ii}^n$ : for  $i = 1, \ldots, N$  do for  $i \in \mathcal{I}(i), i \neq i$  do  $\begin{vmatrix} d_{ij}^n \leftarrow \max\left(\tilde{\lambda}_{\max}(\boldsymbol{n}_{ij}, \boldsymbol{U}_i^n, \boldsymbol{U}_j^n) | \boldsymbol{c}_{ij} \end{vmatrix}, \ \tilde{\lambda}_{\max}(\boldsymbol{n}_{ji}, \boldsymbol{U}_j^n, \boldsymbol{U}_j^n) | \boldsymbol{c}_{ji} \end{vmatrix} \right)$ // Step 2: compute  $d_{ii}^n$  and  $\tau_n$ :  $\tau_n \leftarrow +\infty$ for  $i = 1, \ldots, \mathcal{N}$  do  $| d_{ji}^n \leftarrow -\sum_{j \in \mathcal{I}(i), j \neq i} d_{ii}^n, \qquad \tau_n \leftarrow \min\left(\tau_n, -c_{cfL} \frac{m_i}{2d^n}\right)$ // Step 3: perform update for  $i = 1, \ldots, N$  do for  $j \in \mathcal{I}(i)$  do  $\begin{bmatrix} \mathbf{U}_{i}^{n+1} \leftarrow \mathbf{U}_{i}^{n} + \frac{\tau_{n}}{m_{i}} \left( \sum_{j \in \mathcal{I}(i)} \mathrm{f}(\mathbf{U}_{i}^{n}) \cdot \mathbf{c}_{ij} - \sum_{j \in \mathcal{I}(i)} d_{ij}^{n} \mathbf{U}_{i}^{n} \right) \end{bmatrix}$ 

// Step 4: MPI synchronization
U.update\_ghost\_values()

### Parallelization approach (step-69)

- MPI parallelization via parallel::distributed::Triangulation LinearAlgebra::distributed::Vector
- Precompute m<sub>i</sub> and c<sub>ij</sub>.
   (This is the only place where finite elements enter)
- Distribute work onto threads with parallel::apply\_to\_subranges()
- Avoids global to (MPI) local index translations.
- (Asynchronous IO.)

```
const auto on subranges =
  [&1(
    std cxx20::ranges::iota view<unsigned int, unsigned int>::iterator i1.
    const std cxx20::ranges::iota view<unsigned int.
                                       unsigned int>::iterator i2) {
    for (const auto i :
         std cxx20::ranges::iota view<unsigned int, unsigned int>(*i1.
                                                                    *i2))
        const auto U i = gather(U, i):
        for (auto it = sparsity.begin(i): it != sparsity.end(i): ++it)
            const auto i = it->column():
            if (i \ge i)
            const auto U j = gather(U, j);
            const auto n ii = gather get entry(nii matrix, it);
            const double norm = get_entry(norm_matrix, jt);
            const auto lambda max =
              ProblemDescription<dim>::compute lambda max(U i, U i, n ii):
            double d = norm * lambda_max;
            if (boundary normal map.count(i) != 0 &&
                boundary normal map.count(i) != 0)
                const auto n ji = gather(nij matrix, j, i):
                const auto lambda max 2 =
                  ProblemDescription<dim>::compute_lambda_max(U_j,
                                                               n_{ii}:
                const double norm 2 = norm matrix(j, i);
                d = std::max(d, norm 2 * lambda max 2);
            set_entry(dij_matrix, jt, d);
            dij_matrix(j, i) = d;
          }
      3
  };
parallel::apply to subranges(indices relevant.begin(),
                             indices relevant.end().
                              on subranges.
                              40\overline{9}6):
```

#### MPI local index translations:

```
TimerOutput::Scope scope(
    computing_timer,
    "offline data - create sparsity pattern and set up matrices"):
 DynamicSparsityPattern dsp(n locally relevant, n locally relevant);
 const auto dofs per cell = discretization->finite element.dofs per cell:
 std::vector<types::global dof index> dof indices(dofs per cell):
 for (const auto &cell : dof handler.active cell iterators())
      if (cell->is artificial())
       continue
     /* We transform the set of global dof indices on the cell to the
      * corresponding "local" index range on the MPI process: */
      cell->get dof indices(dof indices);
     std::transform(dof_indices.begin(),
                     dof indices.end(),
                     dof indices.begin(),
                     [&](types::global_dof_index index) {
                       return partitioner->global to local(index);
     /* And simply add, for each dof, a coupling to all other "local"
       * dofs on the cell: */
     for (const auto dof : dof indices)
       dsp.add_entries(dof, dof_indices.begin(), dof_indices.end());
 sparsity pattern.copy from(dsp);
 lumped_mass_matrix.reinit(sparsity_pattern);
 norm matrix.reinit(sparsity pattern);
 for (auto &matrix : cii matrix)
    matrix.reinit(sparsity pattern):
 for (auto &matrix : nii matrix)
    matrix.reinit(sparsity pattern):
template <std::size t k>
DEAL II ALWAYS INLINE inline Tensor<1. k>
gather(const std::array<LinearAlgebra::distributed::Vector<double>, k> &U.
       const unsigned int
 Tensor<1, k> result:
 for (unsigned int j = 0; j < k; ++j)
result[j] = U[j].local_element(i);</pre>
 return result:
```

#### Asynchronous IO:

auto data\_out = std::make\_shared<DataOut<dim>>();

data\_out->attach\_dof\_handler(offline\_data.dof\_handler);

const auto &component\_names = ProblemDescription<dim>::component\_names;

```
for (unsigned int i = 0; i < problem_dimension; ++i)
    data_out->add_data_vector(output_vector[i], component_names[i]);
```

```
const auto output_worker = [this, name, t, cycle, checkpoint, data_out]() {
    if (checkpoint)
```

```
const unsigned int i =
discretization.triangulation.locally_owned_subdomain();
std::string filename =
name + "-checkpoint-" + Utilities::int_to_string(1, 4) + ".archive";
```

```
std::ofstream file(filename, std::ios::binary | std::ios::trunc);
```

```
boost::archive::binary_oarchive oa(file);
oa << t < cycle;
for (const auto &it1 : output_vector)
for (const auto &it2 : it1)
oa << it2;</pre>
```

```
DataOutBase::VtkFlags flags(t,
cycle,
```

```
true,
DataOutBase::VtkFlags::best_speed);
```

```
data_out->set_flags(flags);
```

```
data_out->write_vtu_with_pvtu_record(
    "", name + "-solution", cycle, mpi_communicator, 6);
```

```
;
```

```
if (asynchronous_writeback)
```

```
'def DEAL_II_WITH_THREADS
background_thread_state = std::async(std::launch::async, output_worker);
se AssertThrow(
false,
ExcMessage(
    "\"asynchronous_writeback\" was set to true but deal.II was built "
    "without thread support (\"DEAL II_WITH_THREADS=false\")."));
```



### ... and beyond

### ... and beyond

$$m_{i}\left(\boldsymbol{U}_{i}^{L,n+1}-\boldsymbol{U}_{i}^{n}\right) = \tau_{n}\sum_{j\in\mathcal{I}(i)}\left(-\operatorname{f}(\boldsymbol{U}_{j}^{n})\cdot\boldsymbol{c}_{ij}+d_{ij}^{L,n}\left(\boldsymbol{U}_{j}^{n}-\boldsymbol{U}_{i}^{n}\right)\right).$$

$$\sum_{j\in\mathcal{I}(i)}m_{ij}\left(\boldsymbol{U}_{j}^{H,n+1}-\boldsymbol{U}_{j}^{n}\right) = \tau_{n}\sum_{j\in\mathcal{I}(i)}\left(-\operatorname{f}(\boldsymbol{U}_{j}^{n})\cdot\boldsymbol{c}_{ij}+d_{ij}^{L,n}\frac{\boldsymbol{\alpha}_{i}^{n}+\boldsymbol{\alpha}_{j}^{n}}{2}\left(\boldsymbol{U}_{j}^{n}-\boldsymbol{U}_{i}^{n}\right)\right),$$

with a suitable indicator  $\alpha_i$ .

- The low-order  $\boldsymbol{U}_{i}^{L,n+1}$  is robust, the high-order  $\boldsymbol{U}_{i}^{H,n+1}$  is not.
- Key idea: Invariant-domain preserving convex Limiting <sup>3</sup>

$$\boldsymbol{U}_{i}^{H,n+1} - \boldsymbol{U}_{i}^{L,n+1} = \sum_{j \in \mathcal{I}(i)} \boldsymbol{P}_{ij}^{n}, \text{ where } \boldsymbol{P}_{ij}^{n} = \dots$$
$$\boldsymbol{U}_{i}^{n+1} - \boldsymbol{U}_{i}^{L,n+1} = \sum_{j \in \mathcal{I}(i)} \boldsymbol{l}_{ij}^{n} \boldsymbol{P}_{ij}^{n}, \quad 0 \leq \boldsymbol{l}_{ij}^{n} \leq 1.$$

<sup>3</sup>Guermond, Nazarov, Popov, Tomas, *Second-order invariant domain preserving approximation of the Euler equations using convex limiting*, SIAM J. Sci. Comput. 40 (2018)



## Coming soon...

#### https://github.com/conservation-laws/



#### Conservation Laws

℃ https://conservation-laws.43-1.org 🛛 conservation-laws@43-1.org



🗇 Packages 🛛 💄 People 💈

le 2 🕅 Teams

💷 Projects 🛛 🔅 Settings

This organization has no repositories.

Create a new repository

## Thank you for your attention!

2D 38M gridpoints: https://www.youtube.com/watch?v=xIwJZlsXpZ4 3D 1.8B gridpoints: https://www.youtube.com/watch?v=vBCRAF\_c8m8



https://www.dealii.org/



https://github.com/conservation-laws/